

# 配管パイプ・屋内配管

## 配管パイプ TP-A (JIS G 3459) SUS304

■単位：kg/m

呼び径	外径/厚み	1.0	1.2	1.5	2.0	2.5	3.0	3.5	3.7	4.0	4.5	5.0	5.1	5.2	5.5	6.0	6.5	6.6	7.0	7.1	7.6	8.2
A	B	mm																				
		6	0.125																			
		8	0.174																			
		10	0.224	0.318																		
6	1/8	10.5	0.237	0.336	0.423																	
		12	0.274	0.392	0.498																	
8	1/4	13.8	0.377	0.460	0.588	0.807																
		16	0.374	0.542	0.697																	
10	3/8	17.3	0.590	0.762	0.922	1.07																
		19	0.448	0.654	0.847																	
		20		0.691	0.897																	
15	1/2	21.7	0.755	0.981	1.20	1.40	1.66															
		25	0.878	1.15																		
		25.4	0.893	1.17	1.67																	
20	3/4	27.2	0.960	1.26	1.54	1.81																
		30	1.06	1.39	2.02																	
		32	1.14	1.49	2.17																	
25	1	34	1.21	1.59	1.96	2.32	2.66	2.99														
		38	1.36	1.79	2.62																	
32	1 1/4	42.7	1.54	2.03	2.97	3.42	3.85															
40	1 1/2	48.6	1.76	2.32	3.41	3.93	4.44	5.53														
		50.8	1.84	2.43	3.57																	
50	2	60.5	2.20	2.91	4.30	4.97	5.63	7.54														
65	2 1/2	76.3	3.70	5.48	6.35	7.20	8.88	9.21	12.1													
80	3	89.1	4.34	6.43	8.48	11.5	15.4															
90	3 1/2	101.6	4.96	7.37	9.72	11.0	13.6	16.2														
100	4	114.3	5.59	8.32	11.0	13.6	16.2	21.9														
125	5	139.8	10.2	11.9	13.5	16.8	21.9															
150	6	165.2	12.1	14.1	16.1	20.0	28.0															
200	8	216.3	15.9	21.2	26.3	34.0	42.5															
250	10	267.4	19.8	26.2	42.2																	
300	12	318.5	23.6	31.3	35.2	50.5																

※定尺は4,000mm (一部6,000mmもあります)

※上記以外のサイズ・鋼種 (316・316L) については、お問い合わせください。

■ スケジュール5S ■ スケジュール10S ■ スケジュール20S ■ スケジュール10S・20S ■ スケジュール40 ■ スケジュール80

寸法公差基準表	外径	φ30mm未満	±0.3mm	厚み	t 2.0mm未満	±0.2mm
		φ30mm以上	±1%		t 2.0mm以上	±10%

## 屋内配管 (寸法、外径の許容差及び重量)

JISG 3448 SUS304TP-D, SUS316TP-D

■単位：mm

呼び方		外径	長さ	外径の許容差	厚み	重量 kg/m		呼び方		外径	長さ	外径の許容差	厚み	重量 kg/m	
Su	A・Su (1)					304	316	Su	A・Su (1)					304	316
13	-	15.88	4,000	0	0.8	0.301	0.303	80	-	89.1	4,000	±1%	2.0	4.34	4.37
20	-	22.22	//	0	1.0	0.529	0.532	100	-	114.3	//	±1%	2.0	5.59	5.63
25	-	28.58	//	0	1.0	0.687	0.691	125	-	139.8	//	±1%	2.0	6.87	6.91
30	25	34.0	//	±0.20mm	1.2	0.980	0.986	150	-	165.2	//	±1%	3.0	12.1	12.2
40	32	42.7	//	±0.20mm	1.2	1.24	1.25	200	-	216.3	//	±1%	3.0	15.9	16.0
50	40	48.6	//	±0.25mm	1.2	1.42	1.43	250	-	267.4	//	±1%	3.0	19.8	19.9
60	50	60.5	//	±0.25mm	1.5	2.20	2.21	300	-	318.5	//	±1%	3.0	23.6	23.8
75	65	76.3	//	±1%	1.5	2.79	2.81								

■は受注生産

注(1) 呼び方A・Suは、JIS G 3542 (配管用炭素鋼鋼管) の呼び方Aに準じたもので、当分の間は併用しても差し支えないものである。  
試験圧力：水圧25kgf/cm<sup>2</sup>